



## Safety Data Sheet

bluechem   
GROUP

according to Regulation (EC) No 1907/2006

### Triple X Air Intake System Cleaner Petrol

Print date: 16.12.2015

Product code: 1388

Page 1 of 11

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Triple X Air Intake System Cleaner Petrol

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Cleaning agent for Fuel Systems

##### 1.3. Details of the supplier of the safety data sheet

Company name:	CTP-GmbH	
Street:	Saalfelder Strasse 35	
Place:	D-07338 Leutenberg	
Telephone:	+4936734/230-0	Telefax: +4936734/230-22
e-mail:	hotline@ctp-gmbh.de	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +4936734/230-19
Internet:	www.ctp-gmbh.de	

##### 1.4. Emergency telephone number:

For Germany: +49-361-730730 (24 hours/7 days)

##### Further Information

Article Number: 33371

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage.

Harmful if inhaled.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

##### 2.2. Label elements

###### Regulation (EC) No. 1272/2008

###### Hazardous components which must be listed on the label

2-methylpropan-1-ol; iso-butanol

xylene

Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates

phenole, ethoxylised

Signal word: Danger

**Triple X Air Intake System Cleaner Petrol**

Print date: 16.12.2015

Product code: 1388

Page 2 of 11

**Pictograms:****Hazard statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Surface tension compounds  
Detergents, Dispersants  
Synthetic agent combinations  
Anti wear agents not classified

**Triple X Air Intake System Cleaner Petrol**

Print date: 16.12.2015

Product code: 1388

Page 3 of 11

**Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
78-83-1	2-methylpropan-1-ol; iso-butanol	30 - < 35 %
	201-148-0	603-108-00-1
	Flam. Liq. 3, STOT SE 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3; H226 H335 H315 H318 H336	
1330-20-7	xylene	25 - < 30 %
	215-535-7	601-022-00-9
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315	
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates	20 - < 25 %
	919-857-5	01-2119463258-33
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066	
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates	5 - < 10 %
	920-134-1	01-2119480153-44
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411 EUH066	
N/A	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)	5 - < 10 %
	Aquatic Chronic 2; H411	
N/A	Low boiling point naphtha - unspecified, Solvent naphtha (petroleum), light arom. Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline),hydrotreated heavy	5 - < 10 %
	918-668-5	01-2119455851-35
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066	
37205-87-1	phenole, ethoxylised	1 - < 5 %
	Acute Tox. 4, Eye Dam. 1, Aquatic Chronic 2; H302 H318 H411	

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Move victim to fresh air. Put victim at rest and keep warm.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

**After contact with skin**

Take off immediately all contaminated clothing, including underwear and shoes .

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

**After contact with eyes**

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

**Triple X Air Intake System Cleaner Petrol**

Print date: 16.12.2015

Product code: 1388

Page 4 of 11

**After ingestion**

Let water be drunken in little sips (dilution effect). Consult physician.

**4.2. Most important symptoms and effects, both acute and delayed**

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**4.3. Indication of any immediate medical attention and special treatment needed**

Warning about danger of aspiration.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition. - No smoking.

**6.2. Environmental precautions**

Beat down gas/vapours/mist with water spray.

Do not empty into drains or the aquatic environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Prevent spreading of spillages (e.g. by oil barrier).

Wipe up with absorbent material (eg. cloth, fleece).

**6.4. Reference to other sections**

No data

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

**Advice on protection against fire and explosion**

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

**Triple X Air Intake System Cleaner Petrol**

Print date: 16.12.2015

Product code: 1388

Page 5 of 11

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

**Further information on storage conditions**

Packaging materials: metal.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-83-1	2-Methylpropan-1-ol	50	154		TWA (8 h)	WEL
		75	231		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

**8.2. Exposure controls**

**Protective and hygiene measures**

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

**Eye/face protection**

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

**Hand protection**

Tested protective gloves are to be worn: Butyl rubber. (DIN EN 374)

**Skin protection**

Wear suitable solvent-proof protective clothing according to EN 465.

**Respiratory protection**

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state: liquid  
 Colour: transparent  
 Odour: aromatic

**Test method**

**Changes in the physical state**

Initial boiling point and boiling range: 110 - 120 °C

Flash point: 24 °C



## Safety Data Sheet

bluechem   
GROUP

according to Regulation (EC) No 1907/2006

### Triple X Air Intake System Cleaner Petrol

Print date: 16.12.2015

Product code: 1388

Page 6 of 11

Lower explosion limits:	0,6 vol. %
Upper explosion limits:	12 vol. %
Ignition temperature:	> 200 °C
Vapour pressure: (at 20 °C)	20 hPa
Density (at 20 °C):	0.82 - 0.84 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	insoluble

#### **Solubility in other solvents**

Organic solvents

#### **9.2. Other information**

No data

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

No information available.

#### **10.2. Chemical stability**

No decomposition when used as intended.

#### **10.3. Possibility of hazardous reactions**

No dangerous reactions are known.

#### **10.4. Conditions to avoid**

Only use the material in places where open light, fire and other flammable sources can be kept away.

#### **10.5. Incompatible materials**

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

#### **10.6. Hazardous decomposition products**

Carbon monoxide (CO).

Carbon dioxide (CO<sub>2</sub>).

### **SECTION 11: Toxicological information**

#### **11.1. Information on toxicological effects**

## Triple X Air Intake System Cleaner Petrol

Print date: 16.12.2015

Product code: 1388

Page 7 of 11

### Acute toxicity

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
78-83-1	2-methylpropan-1-ol; iso-butanol				
	oral	LD50	> 2830 mg/kg	Rat	
	dermal	LD50	> 2000 mg/kg	Rat	
	inhalative (4 h) vapour	LC50	> 24 mg/l	Rat	
1330-20-7	xylene				
	oral	LD50	4300 mg/kg	Rat	
	dermal	LD50	3200 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	21,7 mg/l	Rat	
	inhalative aerosol	ATE	1,5 mg/l		
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates				
	oral	LD50	>5000 mg/kg	Rat	
	dermal	LD50	>5000 mg/kg	Rabbit	
	inhalative (4 h) aerosol	LC50	>5 mg/l	Rat	
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates				
	oral	LD50	>5000 mg/kg	Rat	
	dermal	LD50	>5000 mg/kg	Rabbit	
	inhalative (4 h) aerosol	LC50	>5 mg/l	Rat	
N/A	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)				
	oral	LD50	>5000 mg/kg	Rat	
	dermal	LD50	>2000 mg/kg	Rabbit	
N/A	Low boiling point naphtha - unspecified, Solvent naphtha (petroleum), light arom. Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline),hydrotreated heavy				
	oral	LD50	>3000 mg/kg	Rat	
	dermal	LD50	>3160 mg/kg	Rat	
37205-87-1	phenole, ethoxylised				
	oral	LD50	2000 mg/kg	Rat	

### Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion:

Harmful: may cause lung damage if swallowed.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Triple X Air Intake System Cleaner Petrol**

Print date: 16.12.2015

Product code: 1388

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
78-83-1	2-methylpropan-1-ol; iso-butanol					
	Acute fish toxicity	LC50	1430 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50	1250 mg/l		Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50	1439 mg/l	48 h	Daphnia magna	
1330-20-7	xylene					
	Acute fish toxicity	LC50	26,7 mg/l	96 h	Pimephales promelas	
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates					
	Acute fish toxicity	LC50	>1000 mg/l	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50	>1000 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	1000 mg/l	48 h	Daphnia magna	
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates					
	Acute fish toxicity	LC50	>1000 mg/l	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50	>1000 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	1000 mg/l	48 h	Daphnia magna	
N/A	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)					
	Acute fish toxicity	LC50	1-10 mg/l	96 h	Fish	
	Acute algae toxicity	ErC50	10-100 mg/l	72 h	Algae	
37205-87-1	phenole, ethoxylised					
	Acute fish toxicity	LC50	1-10 mg/l	96 h	Brachydanio rerio	
	Acute algae toxicity	ErC50	1-10 mg/l	72 h	Scenedesmus subspicatus	

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

Swims on the water.

Low potential of bio-accumulation.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
78-83-1	2-methylpropan-1-ol; iso-butanol	0,79

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

No information available.

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Advice on disposal**

Do not dispose with household waste.

Do not empty into drains or the aquatic environment.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal



**Triple X Air Intake System Cleaner Petrol**

Print date: 16.12.2015

Product code: 1388

Page 9 of 11

companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.

**Contaminated packaging**

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S.
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601 640E
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S.
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601 640E
Limited quantity:	5 L
Excepted quantity:	E1

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S.
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Marine pollutant:	-
Special Provisions:	223, 274, 955

**Triple X Air Intake System Cleaner Petrol**

Print date: 16.12.2015

Product code: 1388

Page 10 of 11

Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-E, S-E

**Air transport (ICAO)**

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

No information available.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

Contains:  
> 30 % aliphatic hydrocarbons  
15 - 30 % aromatic hydrocarbons  
< 5 % phenols and halogenated phenols

**National regulatory information**

Water contaminating class (D): 2 - water contaminating

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.



## Safety Data Sheet

bluechem   
GROUP

according to Regulation (EC) No 1907/2006

### Triple X Air Intake System Cleaner Petrol

Print date: 16.12.2015

Product code: 1388

Page 11 of 11

H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*